


Vane Air Motors

Performance Overview


VANE AIR MOTOR										
Model	Operation Data							Maximum Torque		
	Max output power		Torque at max output		Max Speed	Max Air Consumption		Max Speed	Max Torque	
	hp	kw	Nm	lb.in.	rpm	m³/h	cfm	rpm	Nm	lb.in
HX1AM	0.45	0.33	0.31	2.75	10000	35.1	20.5	650	0.65	5.60
HX1UP	0.45	0.33	0.58	5.25	6000	47	27	500	0.68	6.00
HX2AM	0.93	0.68	2.20	19.50	3000	49.5	30	350	3.05	26.10
HX4AM	1.70	1.30	4.10	36.00	3000	132.5	78	300	6.3	56.00
HX6AM	4.00	3.00	10.00	84.00	3000	228	128	300	13	115.00
HX8AM	5.25	3.90	14.40	132.00	2500	293	175	300	21	185.00
HX16AM	9.50	7.00	34.0	290.00	2000	475	275	300	43	372.00

HX1AM AIR MOTOR


HX1AM-NRV (Hub mounting)



HX1UP-NCW (Hub mounting)





HX1UP-NRV (Hub mounting)





HX2AM AIR MOTOR



HX2AM-H (Foot mounting)





HX2AM-V (Hub & Face mounting)



HX2AM-F110 (IEC flange mounting)




HX2AM-F114.3 (NEMA flange mounting)




XH4AM AIR MOTOR


HX4AM-H (Foot mounting)




HX4AM-V (Face mounting)



HX4AM-F110 (IEC flange mounting)




HX4AM-F114.3 (NEMA flange mounting)




XH6AM AIR MOTOR



HX6AM-H (Foot mounting)





HX6AM-V (Face mounting)



HX6AM-F130 (IEC flange mounting)





HX6AM-F114.3 (NEMA flange mounting)





XH8AM AIR MOTOR



HX8AM-H (Foot mounting)





HX8AM-V (Face mounting)



HX8AM-F130 (IEC flange mounting)




HX8AM-F114.3 (NEMA flange mounting)




XH16AM AIR MOTOR

HX16AM-FRV-13 (Foot & NEMA flange mounting)




HX16AM-FRV-2 (Foot & Face mounting)




OILLESS VANE AIR MOTOR

Model	Operation Data								Maximum Torque	
	Max output power		Torque at Max output		Max speed	Max Air Consumption		Max speed	Max Torque	
	hp	kw	Nm	lb.in.	rpm	m ³ /h	cfm	rpm	Nm	lb.in.
HXNL32	0.42	0.31	1.5	13.5	2000	51	30	300	2.5	21
HXNL42	0.82	0.61	2.9	25.5	2000	70	41	500	5.0	44
HXNL52	2.5	1.86	8.9	78.75	2000	115	68	500	11.3	100


HXNL32 (Hub & Foot mounting)



HXNL42 (Hub & Foot mounting)





HXNL52 (Hub & Foot mounting)





STAINLESS STEEL AIR MOTOR

Model	Operation Data							Maximum Torque		
	Max output power		Torque at Max output		Max speed	Max Air Consumption		Max speed	Max Torque	
	hp	kw	Nm	lb.in.	rpm	m³/h	cfm	rpm	Nm	lb.in.
HX1AM-V-S-113	0.45	0.33	0.31	2.75	10000	35.1	20.5	650	0.65	5.60
HX1AM-VF-S-113	0.45	0.33	0.31	2.75	10000	35.1	20.5	650	0.65	5.60
HX1AM-V-S-125	0.45	0.33	0.31	2.75	10000	35.1	20.5	650	0.65	5.60
HX4AM-NRV-251SS	1.70	1.30	4.1	36.00	3000	132.5	78	300	6.3	56.00



HX1AM-V-S-113 (Hub mounting)




HX1AM-VF-S-113 (Face mounting)



HX1AM-V-S-127 (Flange mounting)




HX4AM-NRV-251SS (Face mounting)




AIR GEAR MOTOR

Model	Gear Ratio	Operation Data							Maximum Torque		
		Max output power		Torque at Max output		Max Speed	Max Air Consumption		Max Speed	Max Torque	
		hp	kw	Nm	lb.in.	rpm	m ³ /h	cfm	rpm	Nm	lb.in.
HX1AM-NRV-95-GR15	15:1	0.34	0.26	7.1	62	350	36	21	30	8.1	72
HX1UP-NRV-16-GR15	15:1	0.32	0.23	5.5	49	400	36	21	30	8.0	71
HX4AM-RV-10	10:1	1.26	0.94	31	274	300	98	57.5	30	48	425
HX4AM-RV-15	15:1	1.25	0.9	45.2	400	200	102	60	20	72	640
HXWG01	20:1	0.64	0.48	21	172	110	34	20	12	28	240
HXWG02	20:1	0.90	0.68	29	256	150	46	27	17	40	343.5


HX1AM-NRV-95-GR15 (Face mounting)



HX1UP-NRV-16-GR15 (Face mounting)




HX4AM-RV-10 (Face or Foot mounting)




AIR GEAR MOTOR

HX4AM-RV-15 (Face or Foot mounting)



HXWG01 (Base mounting)



HXWG02 (Base mounting)

